

WARWICK INDUSTRIES INC

DISCLOSURE AND ACKNOWLEDGEMENT

HOW TO USE 2-1/4 PRESSURE POTS PROPERLY

WARNING: Always release the pot's air pressure PRIOR to opening the lid. The pressure pots (tank-25n and tank-26n) might explode if you do not release the pot's air pressure prior to opening the lid, which will cause substantial injuries to you and others nearby.

- To release the pot's air pressure, use relief valve (left turn the screw) and the safety valve (pull up the o ring). Both of these valves can be found on the top of the lid. (see parts break down attached with pot)
- Always keep the relief valve and safety valve CLEAN at all times.
- Always check and make sure that the two valves are in working condition when the air pressure reaches 5 PSI before increasing the pressure any further.
- DO NOT attempt to repair the safety valve. If the safety valve does not work as it should, replace it with new one by calling your distributor or contact us at 1-800-418-3921

By signing at the bottom, the customer acknowledges that this disclosure has been read and understood.

WARWICK HEREBY DISCLAIMS ANY LIABILITIES, AND USER IS SOLELY RESPONSIBLE FOR ANY LOSSES, RESULTED FROM OR ATTRIBUTED TO DAMAGES OR INJURIES THAT ARE CAUSED BY THE FAILURE OF OPERATING THE PRODUCT IN A MANNER CONSISTENT WITH THE INSTRUCTIONS PROVIDED HEREIN

DISTRIBUTOR

CUSTOMER NAME:

NAME

DATE

NAME

DATE

PLEASE FAX THIS COPY TO 1-800-524-0579 WHILE POTS SOLD
(Spanish version is available upon request.)

DISTRIBUTOR AGREES TO INDEMNIFY, HOLD HARMLESS, AND DEFEND WARWICK AGAINST ANY LIABILITY ARISING OUT OF DAMAGES AND INJURIES THAT ARE RESULTED FROM AND ATTRIBUTED TO FAILURE TO PROVIDE USER THE WARNING AS PROVIDED ABOVE.